

# Three Phase Inverter with Synergy Technology For Europe

SE50K / SE66.6K / SE90K / SE100K / SE120K

INVERTERS



## Powered by unique pre-commissioning process for rapid system installation

- Pre-commissioning feature for automated validation of system components and wiring during the site installation process and prior to grid connection
- Easy 2-person installation with lightweight, modular design (each inverter consists of 2 or 3 Synergy Units and one Synergy Manager)
- Independent operation of each Synergy Unit enables higher uptime and easy serviceability
- Built-in thermal sensors detect faulty wiring ensuring enhanced protection and safety
- Built-in arc fault protection and optional rapid shutdown
- Built-in PID mitigation for maximized system performance
- Monitored\* and field-replaceable surge protection devices, to better withstand surges caused by lightning or other events: integrated RS485 and Type 2 DC SPDs, optional Type 2 AC SPD
- Optional integrated DC safety switch eliminates the need for external DC isolators
- Built-in module-level monitoring with Ethernet or cellular communication for full system visibility

\*Applicable only for DC and AC SPDs

# / Three Phase Inverter with Synergy Technology

## For Europe

SE50K / SE66.6K / SE90K / SE100K / SE120K

Applicable to Inverter with Part Number	SExxK-xxx0lxxxx				SExxK- xxx8lxxxx	
	SE50K <sup>(1)</sup> For 400V Grid	SE66.6K For 400V Grid	SE90K For 400V Grid	SE100K For 400V Grid	SE120K For 480V Grid	
<b>OUTPUT</b>						
Rated AC Active Output Power	50000 <sup>(2)</sup>	66600	90000	100000	120000	W
Maximum AC Apparent Output Power	50000 <sup>(2)</sup>	66600	90000	100000	120000	VA
AC Output Voltage — Line to Line / Line to Neutral (Nominal)	380 / 220; 400 / 230				480 / 277	Vac
AC Output Voltage — Line to Line Range / Line to Neutral Range	304 - 437 / 176 - 253; 320 - 460 / 184 - 264.5				432 - 529 / 249 - 305	Vac
AC Frequency	50/60 ± 5%					Hz
Maximum Continuous Output Current (per Phase)	72.5	96.5	130.5	145		Aac
AC Output Line Connections	3W + PE, 4W + PE					
Supported Grids	WYE: TN-C, TN-S, TN-C-S, TT, IT; Delta: IT					
Maximum Residual Current Injection <sup>(3)</sup>	200		300			mA
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes					
Total Harmonic Distortion	≤ 3					%
Power Factor Range	+/-0.2 to 1					
<b>INPUT</b>						
Maximum DC Power (Module STC) Inverter / Synergy Unit	87500 / 43750	116550 / 58275	157500 / 52500	175000 / 58300	210000 / 70000	W
Transformer-less, Ungrounded	Yes					
Maximum Input Voltage DC+ to DC-	1000					Vdc
Operating Voltage Range	680 - 1000					Vdc
Maximum Input Current	2 x 36.25	2 x 48.25	3 x 43.5	3 x 48.25	3 x 48.25	Adc
Reverse-Polarity Protection	Yes					
Ground-Fault Isolation Detection	167kΩ sensitivity per Synergy Unit <sup>(4)</sup>					
Maximum Inverter Efficiency	98.3				98.1	%
European Weighted Efficiency	98					%
Nighttime Power Consumption	< 8		<12			W
<b>ADDITIONAL FEATURES</b>						
Supported Communication Interfaces <sup>(5)</sup>	2 x RS485, Ethernet, Wi-Fi (optional), Cellular (optional)					
Smart Energy Management	Export limitation					
Inverter Commissioning	With the SetApp mobile application using built-in Wi-Fi access point for local connection					
Arc Fault Protection	Built-in, user configurable (according to UL1699B)					
Rapid Shutdown	Optional (automatic upon AC Grid Disconnect)					
PID Rectifier	Nighttime, built-in					
RS485 Surge Protection (ports 1 + 2)	Type II, field replaceable, integrated					
DC Surge Protection	Type II, field replaceable, integrated					
AC Surge Protection	Type II, field replaceable, optional					
DC Fuses (Single Pole)	25A, optional					
DC Disconnect Switch	Optional					
Pre-Commissioning	Built-in <sup>(6)</sup>					
<b>STANDARD COMPLIANCE</b>						
Safety	IEC-62109-1, IEC-62109-2, AS3100					
Grid Connection Standards <sup>(7)</sup>	EN50549-1, EN50549-2, VDE-AR-N 4105, VDE-AR-N 4110, VDE V 0126-1-1, CEI 0-21, CEI 0-16, TOR Erzeuger Typ A+B, G99 Type A+B, G99 (NI) Type A+B, VFR 2019					
Emissions	IEC61000-6-2, IEC61000-6-3 Class A, IEC61000-3-11, IEC61000-3-12					
RoHS	Yes					

(1) Only available in Poland and the UK. Refer to: [https://www.solaredge.com/sites/default/files/se\\_inverters\\_supported\\_countries.pdf](https://www.solaredge.com/sites/default/files/se_inverters_supported_countries.pdf)

(2) 49990 in the UK

(3) If an external RCD is required, its trip value must be ≥ 200mA for SE50K/SE66.6K; ≥ 300mA for SE90K, SE100K, SE120K

(4) Where permitted by local regulations

(5) For specifications of the optional communication options, visit <https://www.solaredge.com/products/communication> or the Resource Library webpage:

<https://www.solaredge.com/resource-library>, to download the relevant product datasheet

(6) Not available for P/Ns SExxK-xxxxBPxx

(7) For all standards and certificates download, refer to Certifications category on the Resource Library page: <https://www.solaredge.com/resource-library>

# / Three Phase Inverter with Synergy Technology

## For Europe

SE50K / SE66.6K / SE90K / SE100K / SE120K

Applicable to Inverter with Part Number	SExxK-xxx01xxxx				SExxK-xxx81xxxx
	SE50K <sup>(1)</sup> For 400V Grid	SE66.6K For 400V Grid	SE90K For 400V Grid	SE100K For 400V Grid	SE120K For 480V Grid

INSTALLATION SPECIFICATIONS				
Number of Synergy Units per Inverter	2	3		
AC Wire Cross Section and Outer Diameter: Line/PE (Aluminum or Copper)	Cross section up to 120 / 70 mm <sup>2</sup> ; outer diameter 30-50 / 12-20 mm			
DC Input: Inverter / Synergy Unit <sup>(8)</sup>	8 / 4 MC4 pairs	12 / 4 MC4 pairs		
Dimensions (H x W x D)	Synergy Unit: 558 x 328 x 273 Synergy Manager: 360 x 560 x 295			mm
Weight	Synergy Unit: 32 Synergy Manager: 18			kg
Operating Temperature Range	-40 to +60 <sup>(9)</sup>			°C
Cooling	Fan (user replaceable)			
Noise	< 67			dBA
Protection Rating	IP65 — outdoor and indoor			
Mounting	Brackets provided			

(8) Only MC4 connectors manufactured by Staubli are approved for use

(9) For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note.pdf>

### Accessories - SPDs (purchased separately)

Accessory	PN
AC SPD kit for Synergy Manager (5 units per box)	SE-AC-SPD-SM