

# Test Verification of Conformity

Verification Number: 240900123SHA-V1

On the basis of the tests undertaken, the sample<s> of the below product has been tested by an accredited 3rd party laboratory in accordance to the referenced specification<s>/standard<s> at the time the tests were carried out. This verification is part of the full test report<s> and should be read in conjunction with it <them>.

This document can be used in support of a claim in meeting relevant EU EMC Directive(2014/30/EU) and mandatory Conformity Marking. And in accordance with EU law, the claim is the sole obligation of the Manufacturer/ Importer.

Applicant Name & Address:	Shanghai JA Solar Technology Co., Ltd. No. 118, Lane 3111, West Huancheng Road, Fengxian District, Shanghai, 201401, China
Manufacturer Name & Address:	Same as applicant
Product Description:	Mono Crystalline Silicon Photovoltaic (PV) Modules
Ratings & Principle Characteristics:	See Appendix
Models/Type References:	See Appendix
Brand Name:	JA SOLAR
Relevant Standards:	EN 61000-6-3:2007+A1:2011 EN 61000-6-2:2005
Verification Issuing Office Name & Address:	Intertek Testing Services (Shanghai FTZ) Co., Ltd. Building 86, No.1198, Qinzhou North Road, Shanghai, China
Date of Tests:	-
Test Report Number(s):	220800281SHA-001+A1+A2



## Signature

**Name:** Edwin Xu

**Position:** Assistant Manager

**Date:** September 14, 2024

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## APPENDIX: Test Verification of Conformity

This is an Appendix to Test Verification of Conformity Number: 240900123SHA-V1.

### Models/Type References:

#### Maximum System Voltage: 1500 V DC or 1000 V DC

JAM78S30-xxx/MR, xxx=580 to 605 in steps of 5  
 JAM72S30-xxx/MR, xxx=535 to 565 in steps of 5  
 JAM66S30-xxx/MR, xxx=480 to 510 in steps of 5  
 JAM60S30-xxx/MR, xxx=435 to 460 in steps of 5  
 JAM54S30-xxx/MR, xxx=390 to 425 in steps of 5  
 JAM78S30-xxx/GR, xxx=580 to 615 in steps of 5  
 JAM72S30-xxx/GR, xxx=535 to 565 in steps of 5  
 JAM66S30-xxx/GR, xxx=480 to 515 in steps of 5  
 JAM60S30-xxx/GR, xxx=435 to 470 in steps of 5  
 JAM54S30-xxx/GR, xxx=390 to 425 in steps of 5  
 JAM72S31-xxx/MR, xxx=530 to 565 in steps of 5  
 JAM66S31-xxx/MR, xxx=475 to 500 in steps of 5  
 JAM60S31-xxx/MR, xxx=430 to 455 in steps of 5  
 JAM54S31-xxx/MR, xxx=390 to 425 in steps of 5  
 JAM78S31-xxx/GR, xxx=570 to 600 in steps of 5  
 JAM72S31-xxx/GR, xxx=530 to 555 in steps of 5  
 JAM66S31-xxx/GR, xxx=480 to 505 in steps of 5  
 JAM60S31-xxx/GR, xxx=435 to 460 in steps of 5  
 JAM54S31-xxx/GR, xxx=395 to 425 in steps of 5  
 JAM66S35-xxx/MR, xxx=645 to 670 in steps of 5  
 JAM60S35-xxx/MR, xxx=585 to 610 in steps of 5  
 JAM72S30-xxx/LR, xxx=555 to 585 in steps of 5  
 JAM54S30-xxx/LR, xxx=410 to 440 in steps of 5  
 JAM54S31-xxx/LR, xxx=410 to 440 in steps of 5  
 JAM54S30-xxx/LB, xxx=410 to 440 in steps of 5  
 JAM54S31-xxx/LB, xxx=410 to 435 in steps of 5  
 JAM54S30-xxx/MB, xxx=390 to 425 in steps of 5  
 JAM54S31-xxx/MB, xxx=390 to 425 in steps of 5  
 JAM72S40-xxx/LR, xxx=565 to 620 in steps of 5  
 JAM60S40-xxx/LR, xxx=475 to 510 in steps of 5  
 JAM54S40-xxx/LR, xxx=420 to 460 in steps of 5  
 JAM72S41-xxx/LR, xxx=565 to 610 in steps of 5  
 JAM60S41-xxx/LR, xxx=475 to 510 in steps of 5  
 JAM54S41-xxx/LR, xxx=420 to 460 in steps of 5

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM66S45-xxx/LR, xxx=595 to 630 in steps of 5  
 JAM48S4A-xxx/LR, xxx=430 to 460 in steps of 5  
 JAM48S4B-xxx/LR, xxx=430 to 460 in steps of 5  
 JAM72S42-xxx/LR, xxx=615 to 655 in steps of 5  
 JAM66S42-xxx/MR, xxx=560 to 610 in steps of 5  
 JAM60S42-xxx/LR, xxx=505 to 545 in steps of 5  
 JAM54S42-xxx/LR, xxx=420 to 460 in steps of 5  
 JAM66S43-xxx/MR, xxx=560 to 610 in steps of 5  
 JAM60S43-xxx/LR, xxx=505 to 545 in steps of 5  
 JAM54S43-xxx/LR, xxx=420 to 460 in steps of 5  
 JAM78S40-xxx/MR, xxx=620 to 660 in steps of 5  
 JAM72S40-xxx/MR, xxx=580 to 615 in steps of 5  
 JAM54S40-xxx/MR, xxx=430 to 555 in steps of 5  
 JAM54S41-xxx/MR, xxx=430 to 455 in steps of 5

**Maximum System Voltage: 1500 V DC**

JAM78S30-xxx/MR/1500V, xxx=580 to 605 in steps of 5  
 JAM72S30-xxx/MR/1500V, xxx=535 to 565 in steps of 5  
 JAM66S30-xxx/MR/1500V, xxx=480 to 510 in steps of 5  
 JAM60S30-xxx/MR/1500V, xxx=435 to 460 in steps of 5  
 JAM54S30-xxx/MR/1500V, xxx=390 to 425 in steps of 5  
 JAM78S30-xxx/GR/1500V, xxx=580 to 615 in steps of 5  
 JAM72S30-xxx/GR/1500V, xxx=535 to 565 in steps of 5  
 JAM66S30-xxx/GR/1500V, xxx=480 to 515 in steps of 5  
 JAM60S30-xxx/GR/1500V, xxx=435 to 470 in steps of 5  
 JAM54S30-xxx/GR/1500V, xxx=390 to 425 in steps of 5  
 JAM72S31-xxx/MR/1500V, xxx=530 to 565 in steps of 5  
 JAM66S31-xxx/MR/1500V, xxx=475 to 500 in steps of 5  
 JAM60S31-xxx/MR/1500V, xxx=430 to 455 in steps of 5  
 JAM54S31-xxx/MR/1500V, xxx=390 to 425 in steps of 5  
 JAM78S31-xxx/GR/1500V, xxx=570 to 600 in steps of 5  
 JAM72S31-xxx/GR/1500V, xxx=530 to 555 in steps of 5  
 JAM66S31-xxx/GR/1500V, xxx=480 to 505 in steps of 5  
 JAM60S31-xxx/GR/1500V, xxx=435 to 460 in steps of 5  
 JAM54S31-xxx/GR/1500V, xxx=395 to 425 in steps of 5  
 JAM72S41-xxx/GR/1500V, xxx=545 to 575 in steps of 5  
 JAM66S41-xxx/GR/1500V, xxx=500 to 525 in steps of 5  
 JAM66S35-xxx/MR/1500V, xxx=645 to 670 in steps of 5  
 JAM60S35-xxx/MR/1500V, xxx=585 to 610 in steps of 5  
 JAM72S30-xxx/LR/1500V, xxx=555 to 585 in steps of 5  
 JAM54S30-xxx/LR/1500V, xxx=410 to 440 in steps of 5  
 JAM54S31-xxx/LR/1500V, xxx=410 to 440 in steps of 5  
 JAM54S30-xxx/LB/1500V, xxx=410 to 440 in steps of 5  
 JAM54S31-xxx/LB/1500V, xxx=410 to 435 in steps of 5  
 JAM54S30-xxx/MB/1500V, xxx=390 to 425 in steps of 5

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM54S31-xxx/MB/1500V, xxx=390 to 425 in steps of 5  
 JAM78D30-xxx/MB, xxx=580 to 610 in steps of 5  
 JAM72D30-xxx/MB, xxx=535 to 565 in steps of 5  
 JAM66D30-xxx/MB, xxx=485 to 510 in steps of 5  
 JAM60D30-xxx/MB, xxx=440 to 465 in steps of 5  
 JAM54D30-xxx/MB, xxx=395 to 420 in steps of 5  
 JAM54D31-xxx/MB, xxx=395 to 420 in steps of 5  
 JAM66D35-xxx/MB, xxx=645 to 670 in steps of 5  
 JAM60D35-xxx/MB, xxx=585 to 610 in steps of 5  
 JAM78D40-xxx/GB, xxx=580 to 650 in steps of 5  
 JAM72D40-xxx/GB, xxx=540 to 600 in steps of 5  
 JAM66D40-xxx/GB, xxx=500 to 550 in steps of 5  
 JAM60D40-xxx/GB, xxx=455 to 500 in steps of 5  
 JAM54D40-xxx/GB, xxx=405 to 450 in steps of 5  
 JAM54D41-xxx/GB, xxx=405 to 440 in steps of 5  
 JAM78D30-xxx/GB, xxx=580 to 615 in steps of 5  
 JAM72D30-xxx/GB, xxx=540 to 565 in steps of 5  
 JAM66D30-xxx/GB, xxx=495 to 520 in steps of 5  
 JAM60D30-xxx/GB, xxx=450 to 470 in steps of 5  
 JAM54D30-xxx/GB, xxx=405 to 425 in steps of 5  
 JAM54D31-xxx/GB, xxx=405 to 425 in steps of 5  
 JAM78D40-xxx/MB, xxx=610 to 660 in steps of 5  
 JAM72D40-xxx/MB, xxx=560 to 615 in steps of 5  
 JAM66D40-xxx/MB, xxx=500 to 550 in steps of 5  
 JAM60D40-xxx/MB, xxx=455 to 500 in steps of 5  
 JAM54D40-xxx/MB, xxx=415 to 450 in steps of 5  
 JAM54D41-xxx/MB, xxx=415 to 450 in steps of 5  
 JAM72D40-xxx/HB, xxx=580 to 610 in steps of 5  
 JAM54D40-xxx/HB, xxx=430 to 455 in steps of 5  
 JAM54D41-xxx/HB, xxx=425 to 455 in steps of 5  
 JAM66D46-xxx/HB, xxx=680 to 730 in steps of 5  
 JAM60D46-xxx/HB, xxx=610 to 665 in steps of 5  
 JAM66D47-xxx/HB, xxx=680 to 730 in steps of 5  
 JAM60D47-xxx/HB, xxx=610 to 665 in steps of 5  
 JAM66D45-xxx/LB, xxx=595 to 635 in steps of 5  
 JAM60D45-xxx/LB, xxx=535 to 570 in steps of 5  
 JAM54D45-xxx/LB, xxx=480 to 515 in steps of 5  
 JAM48D4A-xxx/LB, xxx=430 to 460 in steps of 5  
 JAM48D4B-xxx/LB, xxx=430 to 460 in steps of 5  
 JAM72D40-xxx/LB, xxx=580 to 620 in steps of 5  
 JAM60D40-xxx/LB, xxx=470 to 510 in steps of 5  
 JAM54D40-xxx/LB, xxx=430 to 460 in steps of 5  
 JAM60D41-xxx/LB, xxx=470 to 510 in steps of 5  
 JAM54D41-xxx/LB, xxx=425 to 460 in steps of 5  
 JAM72D42-xxx/LB, xxx=605 to 650 in steps of 5  
 JAM66D42-xxx/MB, xxx=540 to 610 in steps of 5

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM60D42-xxx/LB, xxx=495 to 545 in steps of 5  
 JAM60D43-xxx/LB, xxx=495 to 545 in steps of 5  
 JAM54D42-xxx/LB, xxx=450 to 490 in steps of 5  
 JAM54D43-xxx/LB, xxx=450 to 490 in steps of 5  
 JAM78D49-xxx/LB, xxx=585 to 625 in steps of 5  
 JAM72D30-xxx/LB, xxx=555 to 580 in steps of 5  
 JAM54D30-xxx/LB, xxx=415 to 435 in steps of 5  
 JAM54D31-xxx/LB, xxx=415 to 435 in steps of 5  
 JAM66D46-xxx/LB, xxx=680 to 730 in steps of 5  
 JAM60D46-xxx/LB, xxx=610 to 665 in steps of 5  
 JAM66D42-xxx/MR, xxx=540 to 610 in steps of 5  
 JAM66D45-xxx/LR, xxx=595 to 635 in steps of 5  
 JAM54D40-xxx/LR, xxx=430 to 460 in steps of 5  
 JAM54D40-xxx/MR, xxx=415 to 450 in steps of 5  
 JAM78D30-xxx/MB/1500V, xxx=580 to 610 in steps of 5  
 JAM72D30-xxx/MB/1500V, xxx=535 to 565 in steps of 5  
 JAM66D30-xxx/MB/1500V, xxx=485 to 510 in steps of 5  
 JAM60D30-xxx/MB/1500V, xxx=440 to 465 in steps of 5  
 JAM54D30-xxx/MB/1500V, xxx=395 to 420 in steps of 5  
 JAM54D31-xxx/MB/1500V, xxx=395 to 420 in steps of 5  
 JAM66D35-xxx/MB/1500V, xxx=645 to 670 in steps of 5  
 JAM60D35-xxx/MB/1500V, xxx=585 to 610 in steps of 5  
 JAM78D40-xxx/GB/1500V, xxx=580 to 650 in steps of 5  
 JAM72D40-xxx/GB/1500V, xxx=540 to 600 in steps of 5  
 JAM66D40-xxx/GB/1500V, xxx=500 to 550 in steps of 5  
 JAM60D40-xxx/GB/1500V, xxx=455 to 500 in steps of 5  
 JAM54D40-xxx/GB/1500V, xxx=405 to 450 in steps of 5  
 JAM54D41-xxx/GB/1500V, xxx=405 to 440 in steps of 5  
 JAM78D30-xxx/GB/1500V, xxx=580 to 615 in steps of 5  
 JAM72D30-xxx/GB/1500V, xxx=540 to 565 in steps of 5  
 JAM66D30-xxx/GB/1500V, xxx=495 to 520 in steps of 5  
 JAM60D30-xxx/GB/1500V, xxx=450 to 470 in steps of 5  
 JAM54D30-xxx/GB/1500V, xxx=405 to 425 in steps of 5  
 JAM54D31-xxx/GB/1500V, xxx=405 to 425 in steps of 5  
 JAM78D40-xxx/MB/1500V, xxx=610 to 660 in steps of 5  
 JAM72D40-xxx/MB/1500V, xxx=560 to 615 in steps of 5  
 JAM66D40-xxx/MB/1500V, xxx=500 to 550 in steps of 5  
 JAM60D40-xxx/MB/1500V, xxx=455 to 500 in steps of 5  
 JAM54D40-xxx/MB/1500V, xxx=415 to 450 in steps of 5  
 JAM54D41-xxx/MB/1500V, xxx=415 to 450 in steps of 5  
 JAM66D45-xxx/LB/1500V, xxx=595 to 635 in steps of 5  
 JAM60D45-xxx/LB/1500V, xxx=535 to 570 in steps of 5  
 JAM54D45-xxx/LB/1500V, xxx=480 to 515 in steps of 5  
 JAM48D45-xxx/LB/1500V, xxx=430 to 460 in steps of 5  
 JAM48D44-xxx/LB/1500V, xxx=430 to 460 in steps of 5  
 JAM72D40-xxx/LB/1500V, xxx=580 to 620 in steps of 5

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



JAM60D40-xxx/LB/1500V, xxx=470 to 510 in steps of 5  
 JAM54D40-xxx/LB/1500V, xxx=430 to 460 in steps of 5  
 JAM60D41-xxx/LB/1500V, xxx=470 to 510 in steps of 5  
 JAM54D41-xxx/LB/1500V, xxx=425 to 460 in steps of 5  
 JAM72D42-xxx/LB/1500V, xxx=605 to 650 in steps of 5  
 JAM66D42-xxx/MB/1500V, xxx=540 to 610 in steps of 5  
 JAM60D42-xxx/LB/1500V, xxx=495 to 545 in steps of 5  
 JAM60D43-xxx/LB/1500V, xxx=495 to 545 in steps of 5  
 JAM54D42-xxx/LB/1500V, xxx=450 to 490 in steps of 5  
 JAM54D43-xxx/LB/1500V, xxx=450 to 490 in steps of 5  
 JAM78D49-xxx/LB/1500V, xxx=585 to 625 in steps of 5  
 JAM72D30-xxx/LB/1500V, xxx=555 to 580 in steps of 5  
 JAM54D30-xxx/LB/1500V, xxx=415 to 435 in steps of 5  
 JAM54D31-xxx/LB/1500V, xxx=415 to 435 in steps of 5  
 JAM66D46-xxx/LB/1500V, xxx=680 to 730 in steps of 5  
 JAM60D46-xxx/LB/1500V, xxx=610 to 665 in steps of 5

**Maximum System Voltage: 1000 V DC**

JAM78S30-xxx/MR/1000V, xxx=580 to 605 in steps of 5  
 JAM72S30-xxx/MR/1000V, xxx=535 to 565 in steps of 5  
 JAM66S30-xxx/MR/1000V, xxx=480 to 510 in steps of 5  
 JAM60S30-xxx/MR/1000V, xxx=435 to 460 in steps of 5  
 JAM54S30-xxx/MR/1000V, xxx=390 to 425 in steps of 5  
 JAM78S30-xxx/GR/1000V, xxx=580 to 615 in steps of 5  
 JAM72S30-xxx/GR/1000V, xxx=535 to 565 in steps of 5  
 JAM66S30-xxx/GR/1000V, xxx=480 to 515 in steps of 5  
 JAM60S30-xxx/GR/1000V, xxx=435 to 470 in steps of 5  
 JAM54S30-xxx/GR/1000V, xxx=390 to 425 in steps of 5  
 JAM72S31-xxx/MR/1000V, xxx=530 to 565 in steps of 5  
 JAM66S31-xxx/MR/1000V, xxx=475 to 500 in steps of 5  
 JAM60S31-xxx/MR/1000V, xxx=430 to 455 in steps of 5  
 JAM54S31-xxx/MR/1000V, xxx=390 to 425 in steps of 5  
 JAM78S31-xxx/GR/1000V, xxx=570 to 600 in steps of 5  
 JAM72S31-xxx/GR/1000V, xxx=530 to 555 in steps of 5  
 JAM66S31-xxx/GR/1000V, xxx=480 to 505 in steps of 5  
 JAM60S31-xxx/GR/1000V, xxx=435 to 460 in steps of 5  
 JAM54S31-xxx/GR/1000V, xxx=395 to 425 in steps of 5  
 JAM66S35-xxx/MR/1000V, xxx=645 to 670 in steps of 5  
 JAM60S35-xxx/MR/1000V, xxx=585 to 610 in steps of 5  
 JAM72S30-xxx/LR/1000V, xxx=555 to 585 in steps of 5  
 JAM54S30-xxx/LR/1000V, xxx=410 to 440 in steps of 5  
 JAM54S31-xxx/LR/1000V, xxx=410 to 440 in steps of 5  
 JAM54S30-xxx/LB/1000V, xxx=410 to 440 in steps of 5  
 JAM54S31-xxx/LB/1000V, xxx=410 to 435 in steps of 5  
 JAM54S30-xxx/MB/1000V, xxx=390 to 425 in steps of 5

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

JAM54S31-xxx/MB/1000V, xxx=390 to 425 in steps of 5



**Signature**

**Name: Edwin Xu**

**Position: Assistant Manager**

**Date: September 14, 2024**



This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.