

## FoxESS T20 G3

Product code: F.FOX.3F.wifi.00200-G3



Manufacturer	FOXESS
Inverter type	On-grid
Inverter phases	3
Max. AC power	20000
Max. DC power	30000
Output power	20000
Circuit breaker value	50
MPPT	2
Amperage	28
WIFI	Tak
Ethernet	No
Compatible optimizers	Tigo
Warranty	12
CN code number	85044086
Quantity per pallet	14
Country of origin	China
Weight	48
Width	38
Height	48
Depth	19

The T series inverters have been specially designed for three-phase residential installations and smaller commercial installations. They are characterized by unparalleled performance and versatility, which allows for extended periods of energy generation. Three-phase versions of the inverters are available in power ranges from 3 kW to 25 kW. The FoxESS T20-G3 inverter is a three-phase device that guarantees maximum performance, reliability, and long lifespan to the user. Additionally, the FoxESS T20-G3 inverter stands out for its high-quality construction, thanks to the use of components from renowned brands during production. This significantly affects the quality and durability of the inverter's operation. The FoxESS product features a unique radiator and cooling fins integrated into the housing, ensuring optimal contact with heat-generating elements. The cooling fins have a characteristic star shape, which increases the cooling surface.

## **Product variants**

Index Price

G-VOLT 1/3 Generated: 2024-11-23

Index Price

FoxESS T20 G3 F.FOX.3F.wifi.00200-G3 Product prices only visible after login. If you do not have an account, please register.

## **Product description**

The T series inverters have been specially designed for three-phase residential installations and smaller commercial installations. They are characterized by unparalleled performance and versatility, which allows for extended periods of energy generation. Three-phase versions of the inverters are available in power ranges from 3 kW to 25 kW. The FoxESS T20-G3 inverter is a three-phase device that guarantees maximum performance, reliability, and long lifespan to the user. Additionally, the FoxESS T20-G3 inverter stands out for its high-quality construction, thanks to the use of components from renowned brands during production. This significantly affects the quality and durability of the inverter's operation. The FoxESS product features a unique radiator and cooling fins integrated into the housing, ensuring optimal contact with heat-generating elements. The cooling fins have a characteristic star shape, which increases the cooling surface.

Advantages of the three-phase FOXESS T20 G3 inverter / 3-phase SERIES G3:

Flexible configuration, ready for installation, easy to expand

Set with high-voltage FoxESS batteries creates the most efficient connection

IP65 class Designed for installation in any environment

Monitor device operation remotely using the website or mobile application

Technical data of the three-phase FoxESS T20 G3 inverter:

maximum recommended DC power [W]: 30000 W

maximum DC voltage [V]: 1100 V

nominal DC operating voltage [V]: 600 V

maximum input current (input A / input B) [A]: 28 / 28 A

maximum short-circuit current (input A / input B) [A]: 36.4 / 36.4 A

MPPT voltage range [Vdc]: 140 - 1000 V DC

startup voltage [V]: 140 V number of MPPT points: 2 number of inputs for MPPT: 2+2 nominal output power [W]: 20000 W

maximum apparent AC power [VA]: 22000 VA nominal AC grid frequency [Hz]: 50/60, ±5

nominal AC current [A]: 29.00 A maximum AC current [A]: 31.9 A MPPT efficiency [%]: 99.8 % maximum efficiency [%]: 98.6%

dimensions (WxHxD): 480 x 370 x 183.5 mm

weight: 20 kg

degree of protection: IP65 topology: transformerless

pollution degree: II

monitoring module: RS485, WIFI (standard) / GPRS (optional) / 4G (optional) / LAN (optional)

communication: energy meter, DRM, USB update, E-stop

display: LCD display, touch button, application, website

FoxESS is a global leader in the production of photovoltaic inverters. During the production process of energy storage solutions, it utilizes the latest standards, resulting in devices with advanced features and characterized by high performance and reliability during operation.

G-VOLT 3 / 3 Generated : 2024-11-23