

## Flexible UV-resistant conduit with a protective sheath of 1250 N, 25mm diameter, 50m.

Product code: **Inne.peszel.25mm.50m**



Flexible conduit with a diameter of 25 mm, resistant to UV radiation, is a heavy-duty corrugated plastic tube designed for outdoor installation. It features a protective jacket with a strength of 1250 N and an inner coating facilitating cable movement. The outer jacket is made of black plastic that does not spread flames and exhibits high resistance to sudden temperature changes. This type of conduit is particularly suitable for outdoor installation and areas requiring high crush resistance, including underground and concrete installations. Thanks to the special inner coating, cables and wires can be easily routed over longer distances without issues.

### Product variants

Index	Price
<b>Flexible UV-resistant conduit with a protective sheath of 1250 N, 25mm diameter, 50m.</b> Inne.peszel.25mm.50m	Product prices only visible after login. If you do not have an account, please register.

### Product description

Flexible conduit with a diameter of 25 mm, resistant to UV radiation, is a heavy-duty corrugated plastic tube designed for outdoor installation. It features a protective jacket with a strength of 1250 N and an inner coating facilitating cable movement. The outer jacket is made of black plastic that does not spread flames and exhibits high resistance to sudden temperature changes. This type of conduit is particularly suitable for outdoor installation and areas requiring high crush resistance, including underground and concrete installations. Thanks to the special inner coating, cables and wires can be easily routed over longer distances without issues. Physical properties: Material: modified PVC High

crush resistance Medium impact resistance Temperature range from -25°C to +60°C Flexible Flame-retardant  
Corrosion-resistant UV-resistant Technical data: Outer diameter Ø: 25 mm Inner diameter Ø: 18.4 mm Coil length:  
50m Coil weight: 8.7 kg