

CITEL T2 AC Surge Protector

Product code: Zab.OgranicznikAC.CITEL.01



Surge protector for T2 AC networks - CITEL AC-DS44-230 operates at four discharge speeds with a current $I_n = 20\text{kA}$ ($8/20\mu\text{s}$), utilizing a varistor block as the main protective element in each module. Designed for installation in low-voltage switchboards as the second stage of protection against induced surges. It is also available in a version with remote signaling capability (-S).

Product variants

Index	Price
<p>CITEL T2 AC Surge Protector Zab.OgranicznikAC.CITEL.01</p>	<p>Product prices only visible after login. If you do not have an account, please register.</p>

Product description

Surge protector for T2 AC networks - CITEL AC-DS44-230 operates at four discharge speeds with a current $I_n = 20\text{kA}$ ($8/20\mu\text{s}$), utilizing a varistor block as the main protective element in each module. Designed for installation in low-voltage switchboards as the second stage of protection against induced surges. It is also available in a version with remote signaling capability (-S). Advantages of the T2 AC-DS44-230 surge protector:

- Rated voltage $U_n=230\text{V AC}$
- Rated discharge current ($8/20\mu\text{s}$) $I_n=20\text{kA}$ per discharge.
- Maximum discharge current ($8/20\mu\text{s}$) $I_{max}=160\text{kA}$
- Nominal frequency $f_n=50-60\text{Hz}$
- Leakage current $< 1\text{mA}$
- Response time $t_a < 25\text{ns}$

Technical data for T2 AC-DS44-230: AC Voltage [V] 230V AC Maximum continuous operating voltage U_c [V] :255V AC Nominal frequency - f_n [Hz] :50-60Hz Short circuit withstand rating - IISCCR [A] 25000A Thermal disconnecter :internal Maximum fuse [A] :up to 125A (gL/gG) Residual-current device (if present in the network) :type "S" or time-delay Conductor cross-section :2.5-25 mm² (35 mm²) Fault indicator :mechanical, red Remote signaling (FS) :potential-free changeover contact Maximum

switching capacity :250V/0.5A (AC) / 30V/2A (DC) FS connector cross-section :single-/multi-core max. 1.5 mm²
Mounting :TH35 mounting rail Operating temperature range: from -40 to +85°C Degree of enclosure protection: IP20
Enclosure material: PEI UL-94-V0 plastic Control standards: PN-EN 61643-11 - Poland Type 2 surge protector EN 61643-11 - Europe: Low Voltage SPD - Test Class II UL1449 - USA: Low voltage SPD