

TRIPLE MC4 (SOCKET) MC-PV-AZS4 FOR PARALLEL CONNECTIONS

Product code: Inne.MC4.Staubli.trojnikmc4.gniazdo



MC4 tee connector (socket) MC-PV-AZS4 for parallel connections Construction: 2x socket (+) KBT4... → plug (-) KST4

Product variants

Index	Price
TRIPLE MC4 (SOCKET) MC-PV-AZS4 FOR PARALLEL CONNECTIONS Inne.MC4.Staubli.trojnikmc4.gniazdo	Product prices only visible after login. If you do not have an account, please register.

Product description

MC4 tee connector (socket) MC-PV-AZS4 for parallel connections Construction: 2x socket (+) KBT4... → plug (-) KST4
Type of contact 4mm diameter banana connector, made of tin-plated copper, with resilient elements inside the sockets improving electrical contact - Multi-lams® Rated voltage: 1500 V DC (UL) Rated current: 50 A Dielectric strength: 12 kV Ambient temperature: -40°C... +75°C (UL) Max operating temperature: 105°C (STAUBLI) Degree of protection: connection state IP67 disconnection state IP2X Measurement category / pollution degree: CAT III / 2 Contact resistance: ≤ 0.5mΩ Protection class: II Insulation: PC Certificate: UL according to UL 6703 standard - E343181