

# TRIPLE MC4 (PLUG) MC-PV-AZB4 FOR PARALLEL CONNECTIONS

Product code: Inne.MC4.Staubli.trojnikmc4.wtyk



TRIPLE MC4 (PLUG) MC-PV-AZB4 FOR PARALLEL CONNECTIONS Original MC4 AZB4 triple from Staubli (Multi-Contact)  
FFM - 2x socket (-) KST4... → plug (+) KBT4

## Product variants

Index	Price
<b>TRIPLE MC4 (PLUG) MC-PV-AZB4 FOR PARALLEL CONNECTIONS</b> Inne.MC4.Staubli.trojnikmc4.wtyk	<div>Product prices only visible after login. If you do not have an account, please register.</div>

## Product description

TRIPLE MC4 (PLUG) MC-PV-AZB4 FOR PARALLEL CONNECTIONS Original MC4 AZB4 triple from Staubli (Multi-Contact)  
FFM - 2x socket (-) KST4... → plug (+) KBT4  
Technical specifications of the MC4 triple:  
Type of contact: 4mm diameter banana connector, made of tin-plated copper, resilient elements are placed inside the sockets to improve electrical contact  
- Multi-lams®  
Rated voltage: 1500 V DC (UL)  
Rated current: 50 A  
Test voltage: 12 kV  
Ambient temperature: -40°C... +75°C (UL)  
Max operating temperature: 105°C (STAUBLI)  
Degree of protection: IP67 in connection state IP2X in disconnection state  
Measurement category / pollution degree: CAT III / 2  
Contact resistance: ≤ 0.5mΩ  
Protection class: II  
Insulation: PC  
Certificate: UL according to UL 6703 standard - E343181