

TRIPLE MC4 (PLUG) MC-PV-AZB4 FOR PARALLEL CONNECTIONS

Product code: **Inne.MC4.Staubli.trojnikmc4.wtyk**



TRIPLE MC4 (PLUG) MC-PV-AZB4 FOR PARALLEL CONNECTIONS Original MC4 AZB4 triple from Staubli (Multi-Contact) FFM - 2x socket (-) KST4... → plug (+) KBT4

Product variants

Index	Price
TRIPLE MC4 (PLUG) MC-PV-AZB4 FOR PARALLEL CONNECTIONS Inne.MC4.Staubli.trojnikmc4.wtyk	Product prices only visible after login. If you do not have an account, please register.

Product description

TRIPLE MC4 (PLUG) MC-PV-AZB4 FOR PARALLEL CONNECTIONS Original MC4 AZB4 triple from Staubli (Multi-Contact) FFM - 2x socket (-) KST4... → plug (+) KBT4 Technical specifications of the MC4 triple: Type of contact: 4mm diameter banana connector, made of tin-plated copper, resilient elements are placed inside the sockets to improve electrical contact - Multi-lams® Rated voltage: 1500 V DC (UL) Rated current: 50 A Test voltage: 12 kV Ambient temperature: -40°C... +75°C (UL) Max operating temperature: 105°C (STAUBLI) Degree of protection: IP67 in connection state IP2X in disconnection state Measurement category / pollution degree: CAT III / 2 Contact resistance: $\leq 0.5\text{m}\Omega$ Protection class: II Insulation: PC Certificate: UL according to UL 6703 standard - E343181