

## FRONIUS SYMO 6.0-3M

Product code: F.Fronius.3F.wifi.00060-M



Manufacturer	FRONIUS
Inverter type	On-grid
Inverter phases	3
Max. AC power	6000
Output power	6000
Circuit breaker value	16
МРРТ	2
Amperage	16
WIFI	Tak
Ethernet	No
Compatible optimizers	Tigo
Warranty	10
CN code number	85044085
Quantity per pallet	12
Country of origin	Austria
Weight	20
Width	43
Height	64
Depth	20

Thanks to the diverse power classes ranging from 3.0 to 8.2 kW, the three-phase Fronius Symo inverter is an excellent solution for use in installations of various sizes. The SuperFlex Design construction makes the Fronius Symo device perfectly suited for curved or differently structured roofs. Easy internet connection via WLAN or Ethernet interface, as well as the possibility of seamless integration with components from other manufacturers, make the Fronius Symo inverter one of the most "communicative" devices available on the market. Additionally, thanks to the meter connection, dynamic power management and transparent visualization of energy consumption are possible.

## **Product variants**

Index	Price
	Product prices
	only visible after
FRONIUS SYMO 6.0-3M	login. If you do
F.Fronius.3F.wifi.00060-M	not have an
	account, please
	register.

# **Product description**

G-VOLT 1/3 Generated: 2024-09-20

Thanks to the diverse power classes ranging from 3.0 to 8.2 kW, the three-phase inverter Fronius Symo represents an excellent solution for applications of various sizes. The SuperFlex Design construction makes the Fronius Symo device perfectly suitable for curved or differently structured roofs. Easy internet connection via WLAN or Ethernet interface, as well as the possibility of seamless integration with components from other manufacturers, make the Fronius Symo inverter one of the most "communicative" devices available on the market. Additionally, thanks to the meter connection, dynamic power management and transparent visualization of energy consumption are possible.

Fronius Symo 6.0-3-M Wlan WEB - Technical data:

#### Input data:

Number of MPP trackers: 2

Maximum input current (Idc max): 16.0/16.0 A

Maximum module field short-circuit current: 31/31 A

DC input voltage range (Udc min - Udc max): 150 - 1000 V

Startup voltage (Udc start): 200 V Rated input voltage (Udc,r): 595 V

MPP voltage range (Umpp min - Umpp max): 195 - 800 V

Usable MPP voltage range: 150 - 800 V

Number of DC connections: 2+2

Maximum photovoltaic generator power (Pdc max): 12 kWpeak

### Output data:

AC rated power (Pac,r): 6000 W

Maximum output power (Pac max): 6000 VA

AC output current (lac nom): 8.7 A

Grid connection (Uac,r): 3~ NPE 400/230, 3~ NPE 380/220 V

AC voltage range (Umin - Umax): 150 - 280 V

Frequency (fr): 50 / 60 Hz

Frequency range (fmin - fmax): 45 - 65 Hz

Non-linear distortion coefficient <3% @Pnom (230/400VAC 50Hz)

Power factor (cos φac,r): 0.85 - 1 ind./cap.

#### General data:

Dimensions / width: 432.5 mm Dimensions / height: 642.5 mm Dimensions / depth: 205.5 mm

Weight: 19.75 kg

Weight with packaging: 23.05 kg

Degree of protection IP 65

Protection class: 1

Overvoltage category (DC/AC) 1): 2 / 3 Nighttime power consumption: < 1 W

Inverter construction concept: Transformerless

Cooling: Regulated ventilation

Installation inside and outside buildings
Ambient temperature range: -25°C - +60°C

Permissible air humidity: 0 - 100 %

DC connection technology: Screw terminals 4x DC+ and 4x DC- 2.5-16 mm<sup>2</sup> (At 16 mm<sup>2</sup> without cable ends.)

AC connection technology: 5-pin screw terminals AC 2.5-16 mm<sup>2</sup> (At 16 mm<sup>2</sup> without cable ends.)

DC insulation measurement: Yes

Behavior in case of overload: Shift of operating point, power limiter

DC disconnector: Yes

DC reverse polarity protection: Yes

Advantages of the Fronius Symo 6.0-3-M Wlan WEB inverter:

SNAPINWERTER mounting system
Integrated data communication
DYNAMIC PEAK MANAGER
SMART GRID READY
SuperFlex Design
Energy impact reduction
Manufactured in Austria

Fronius products come with a standard two-year warranty, which can be extended free of charge to five years by simply registering on the Fronius Solar.web portal. Registering the inverter on Solar.web offers numerous benefits, including:

- Warranty protection for up to 5 years for registered products.
- Free monitoring of photovoltaic installation performance on the Fronius Solar.web portal.
- Regular information on new features, accessories, compatible batteries, and home automation solutions.

G-VOLT 3 / 3 Generated : 2024-09-20