

Fronius Smart Meter TS 63A-3, three-phase meter

Product code: AF.licznik.fronius.02



The Fronius Smart Meter TS 63A-3 is a bidirectional electric energy meter designed to optimize the consumption of self-produced energy and to record the load profile of a household. Collaborating with Fronius inverters, the Fronius Datamanager device, and the Fronius data interface, the Fronius Smart Meter TS enables a clear presentation of energy consumption data. The meter measures the power flow to appliances or to the grid and communicates this information to Fronius inverters and the Fronius Datamanager device using Modbus RTU/RS485 communication.

Product variants

Index	Price
Fronius Smart Meter TS 63A-3, three-phase meter AF.licznik.fronius.02	Product prices only visible after login. If you do not have an account, please register.

Product description

The Fronius Smart Meter TS 63A-3 is a bidirectional electric energy meter designed to optimize the consumption of self-produced energy and to record the load profile of a household. Collaborating with Fronius inverters, the Fronius Datamanager device, and the Fronius data interface, the Fronius Smart Meter TS enables a clear presentation of energy consumption data. The meter measures the power flow to appliances or to the grid and communicates this information to Fronius inverters and the Fronius Datamanager device using Modbus RTU/RS485 communication. Technical specifications of the Fronius Smart Meter TS 63A-3: Nominal voltage: 400 - 415 V Maximum current: 3 x 63 A Cross-section of phase and neutral conductors: 1 - 16 mm² Cross-section of current transformer conductors and communication wires: 0.05 - 4 mm² Own consumption: 1.5 W Starting current: 40 mA Accuracy class: 1 Active energy accuracy: Class B (EN50470) Reactive energy accuracy: Class 2 (EN/IEC 62053-23) Overload (short-term): 20xI_{max}/0.5

s Mounting: Internal mounting (DIN rail) Housing: 4 modules DIN 43880 Protection class: IP 51 (front), IP 20 (connection terminals) Display: 8-digit LCD Operating range: -25 - +55°C Interface to inverter: Modbus RTU (RS485)
