

## The mounting bracket with adjustment for standing seam metal roofing

Product code: **K.40x40.6**



The mounting bracket with adjustment for standing seam metal roofing is designed to connect aluminum profiles or mounting rails with a roof covered in standing seam metal. Thanks to the adjustment opening, precise positioning of the profiles is possible, and they can be secured to the lower channel using a M10 threaded or hammer screw with a flanged nut. The bracket enables non-invasive mounting to the roof surface, meaning it doesn't require drilling or damaging the roof during installation. This makes the product convenient to use and allows for a solid and secure attachment of profiles or mounting rails, which is crucial for the stability of the entire mounting structure.

### Product variants

Index	Price
<b>The mounting bracket with adjustment for standing seam metal roofing</b> K.40x40.6	Product prices only visible after login. If you do not have an account, please register.

### Product description

The mounting bracket with adjustment for standing seam metal roofing is designed to connect aluminum profiles or mounting rails with a roof covered in standing seam metal. Thanks to the adjustment opening, precise positioning of the profiles is possible, and they can be secured to the lower channel using a M10 threaded or hammer screw with a flanged nut. The bracket enables non-invasive mounting to the roof surface, meaning it doesn't require drilling or damaging the roof during installation. This makes the product convenient to use and allows for a solid and secure attachment of profiles or mounting rails, which is crucial for the stability of the entire mounting structure.

Specifications of the mounting bracket with adjustment for standing seam metal roofing: Material: Stainless steel  
Height [mm]: 40 Width [mm]: 40 Length [mm]: 100 Hole diameter [mm]: 2x M8 screw