


## JA Solar JAM72D30 550MB (SFR) (BiFacial)

Product code: PV.jasolar.bifacial.550W



### Od ilości:

≥ 31 pcs.

Product prices only visible after login. If you do not have an account, please register.

≥ 310 pcs.

Product prices only visible after login. If you do not have an account, please register.

JA Solar JAM72D30 550MB is a bifacial 550W photovoltaic panel equipped with SFR (Strong Frame Removal) technology, ensuring lightness and durability. Thanks to its bifacial design, the panel can generate energy from both the front and rear sides, enhancing its efficiency.

Key advantages of the JA Solar JAM72D30 550MB module:

- Bifacial design
- High efficiency
- Lightweight construction
- Weather resistance

Technical specifications of JA Solar JAM72D30 550MB:

Maximum Power (P<sub>mp</sub>): 550 Wp

Open Circuit Voltage (V<sub>oc</sub>): 49.0 V

Short Circuit Current (I<sub>sc</sub>): 11.6 A

Voltage at P<sub>max</sub> (V<sub>mp</sub>): 41.0 V

Current at P<sub>max</sub> (I<sub>mp</sub>): 13.6 A

Module efficiency: 21.5%

Cell type: Monocrystalline Bifacial

Dimensions: 2285 x 1134 x 35 mm

Weight: 28.5 kg

Warranty: 12 years on product, 25 years on linear power degradation

## Product variants

Index

Price

**JA Solar JAM72D30 550MB (SFR) (BiFacial)**

PV.jasolar.bifacial.550W

Product prices only visible after login. If you do not have an account, please register.

## Product description

JA Solar JAM72D30 550MB is a bifacial 550W photovoltaic panel equipped with SFR (Strong Frame Removal) technology, ensuring lightness and durability. Thanks to its bifacial design, the panel can generate energy from both the front and rear sides, enhancing its efficiency.

Key advantages of the JA Solar JAM72D30 550MB module:

- Bifacial design
- High efficiency
- Lightweight construction
- Weather resistance

Technical specifications of JA Solar JAM72D30 550MB:

Maximum Power (Pmpp): 550 Wp

Open Circuit Voltage (Voc): 49.0 V

Short Circuit Current (Isc): 11.6 A

Voltage at Pmax (Vmpp): 41.0 V

Current at Pmax (Impp): 13.6 A

Module efficiency: 21.5%

Cell type: Monocrystalline Bifacial

Dimensions: 2285 x 1134 x 35 mm

Weight: 28.5 kg

Warranty: 12 years on product, 25 years on linear power degradation