

Surface-mounted installation enclosure PHS 24T.

Product code: Zab.obudowa.noark.2x12



Surface-mounted installation enclosure PHS 24T The installation enclosure is designed for various applications, including industrial environments where a high degree of IP protection is required. Its construction allows for easy surface mounting. The delivery includes: enclosure, door, TH-35 rails, N+PE terminals, front cover with cutouts for devices, blanks, and mounting elements.

Product variants

| Index | Price |
|--|--|
| Surface-mounted installation enclosure PHS 24T. Zab.obudowa.noark.2x12 | Product prices only visible after login. If you do not have an account, please register. |

Product description

Surface-mounted installation enclosure PHS 24T The installation enclosure is designed for various applications, including industrial environments where a high degree of IP protection is required. Its construction allows for easy surface mounting. The delivery includes: enclosure, door, TH-35 rails, N+PE terminals, front cover with cutouts for devices, blanks, and mounting elements. Common features of the PHS series: Surface-mounted installation enclosures PHS Rated voltage 400 V AC, 1500 V DC IP65 protection rating 4 to 48 modules 1 to 4 rows Transparent doors Compliant with EN 60670, EN 62208 Rated voltage Un 400 V AC, 1500 V DC Rated current In 63 A Nominal frequency 50 Hz IP65 protection rating Protection class II Rated insulation voltage Ui 690 V AC, 1500 V DC