

BUFFER TANK OEM BLACK v2 200 G without coil

Product code: Zbiornik buforowy OEM BLACK v2 200 G bez węzownicy



Buffer tank for black water, insulated, in OEM BLACK v2 200 G cover, without coil, with a capacity of 200 liters, is used for storing hot boiler water, which can then be used to supply thermal energy to the heating system (e.g., underfloor, wall-mounted, or radiators) when the furnace or boiler is not operating. It serves as a type of heat storage.

Product variants

Index	Price
BUFFER TANK OEM BLACK v2 200 G without coil Zbiornik buforowy OEM BLACK v2 200 G bez węzownicy	Product prices only visible after login. If you do not have an account, please register.

Product description

Buffer tank for black water, insulated, in OEM BLACK v2 200 G cover, without coil, with a capacity of 200 liters, is used for storing hot boiler water, which can then be used to supply thermal energy to the heating system (e.g., underfloor, wall-mounted, or radiators) when the furnace or boiler is not operating. It serves as a type of heat storage. Buffer tanks, including those dedicated to heat pumps, are intended for storing heat for heating purposes and increasing the inertia of the central heating system. This is aimed at reducing cycling (frequent switching on and off) of heat sources and enabling continuous heating of the central heating system when the heating device prioritizes supplying hot water. In the case of air heat pumps, buffer tanks significantly facilitate the defrosting process. Reducing cycling through the use of a buffer tank significantly extends the life of heat pumps, boilers, fireplaces, or other heat sources, and also leads to a reduction in the number of heating device failures. The 200l OEM BLACK v2 200 G buffer tank without coil is dedicated to a single heat source. Technical specifications: Maximum operating temperature: 95°C Maximum operating pressure: 5 bar Energy class: C Weight: 45kg Dimensions: 980x760mm

