

BUFFER TANK OEM BLACK v2 300 G without coil

Product code: Zbiornik buforowy OEM BLACK V2 300G bez wężownicy



Buffer tank for hot water made of black steel, insulated, in OEM BLACK v2 300 G casing without coil, with a capacity of 300 liters, is used for storing hot boiler water, which can then be used to supply thermal energy to the heating system (e.g., underfloor, wall-mounted, or radiators) when the furnace or boiler is not running. It serves as a kind of heat storage.

Product variants

Index	Price
BUFFER TANK OEM BLACK v2 300 G without coil Zbiornik buforowy OEM BLACK V2 300G bez wężownicy	Product prices only visible after login. If you do not have an account, please register.

Product description

Buffer tank for hot water made of black steel, insulated, in OEM BLACK v2 300 G casing without coil, with a capacity of 300 liters, is used for storing hot boiler water, which can then be used to supply thermal energy to the heating system (e.g., underfloor, wall-mounted, or radiators) when the furnace or boiler is not running. It serves as a kind of heat storage. Buffer tanks, including those dedicated to heat pumps, are intended for storing heat for heating purposes and increasing the inertia of the central heating system. This aims, among other things, to reduce the cycling (frequent on/off) of heat sources and to enable continuous heating of the central heating system when the heating device prioritizes supplying hot water. In the case of air-source heat pumps, buffer tanks significantly facilitate the defrosting process of the pump. Reducing cycling through the use of a buffer tank significantly extends the lifespan of heat pumps, boilers, fireplaces, or other heat sources, and also reduces the number of heating equipment failures. The 300L OEM BLACK v2 300 G buffer tank without coil is dedicated to a single heat source. Technical data: Maximum

operating temperature: 95°C Maximum operating pressure: 5 bar Energy class: C Weight: 55kg Dimensions:
1230x760mm