

JA Solar JAM72S30-550MR SF

Product code: **PV.jasolar.sf.550**



JA Solar JAM72S30-550MR SF is a 550W photovoltaic panel ideal for commercial and industrial applications. Thanks to Half-Cell technology and a robust SF (Strong Frame) construction, the module ensures reliability and high efficiency even in harsh weather conditions.

Key advantages of the JA Solar JAM72S30-550MR SF module:

- High efficiency
- Half-Cell technology
- Robust construction
- Low power degradation

Technical specifications of JA Solar JAM72S30-550MR SF:

Maximum Power (P_{mpp}): 550 Wp

Open Circuit Voltage (V_{oc}): 48.8 V

Short Circuit Current (I_{sc}): 11.4 A

Voltage at P_{max} (V_{mpp}): 40.9 V

Current at P_{max} (I_{mpp}): 13.45 A

Module efficiency: 21.4%

Cell type: Monocrystalline Half-Cell

Dimensions: 2278 x 1134 x 35 mm

Weight: 28 kg

Warranty: 12 years on product, 25 years on linear power degradation

Product variants

Index	Price
-------	-------

JA Solar JAM72S30-550MR SF
PV.jasolar.sf.550

Product prices only visible after login. If you do not have an account, please register.

Product description

JA Solar JAM72S30-550MR SF is a 550W photovoltaic panel ideal for commercial and industrial applications. Thanks to Half-Cell technology and a robust SF (Strong Frame) construction, the module ensures reliability and high efficiency even in harsh weather conditions.

Key advantages of the JA Solar JAM72S30-550MR SF module:

- High efficiency
- Half-Cell technology
- Robust construction
- Low power degradation

Technical specifications of JA Solar JAM72S30-550MR SF:

Maximum Power (Pmpp): 550 Wp

Open Circuit Voltage (Voc): 48.8 V

Short Circuit Current (Isc): 11.4 A

Voltage at Pmax (Vmpp): 40.9 V

Current at Pmax (Impp): 13.45 A

Module efficiency: 21.4%

Cell type: Monocrystalline Half-Cell

Dimensions: 2278 x 1134 x 35 mm

Weight: 28 kg

Warranty: 12 years on product, 25 years on linear power degradation