


Jinko Solar JKM430N-54HL4R-BDV 430Wp (BiFacial) (BFR)

Product code: PV.jinko.bf.ntype.430BDV.bifacial



Od ilości:

Product prices only visible after login. If ≥ 36 pcs. you do not have an account, please register.

Product prices only visible after login. If ≥ 360 pcs. you do not have an account, please register.

Jinko Solar JKM430N-54HL4R-BDV is a bifacial 430W photovoltaic panel. High efficiency and the ability to generate energy from both sides of the module make it an excellent choice for a variety of photovoltaic applications. Key advantages of the Jinko Solar JKM430N-54HL4R-BDV module:

- Bifacial design
- BFR technology
- High efficiency
- Lightweight construction

Technical specifications of Jinko Solar JKM430N-54HL4R-BDV:

Maximum Power (Pmpp): 430 Wp Open Circuit Voltage (Voc): 41.5 V Short Circuit Current (Isc): 10.6 A Voltage at Pmax (Vmpp): 34.2 V Current at Pmax (Impp): 12.6 A Module efficiency: 20.3%

Cell type: Monocrystalline Bifacial Dimensions: 1909 x 1134 x 35 mm

Weight: 23 kg

Warranty: 12 years on product, 25 years on linear power degradation

Product variants

Index Price

G-VOLT 1/2 Generated: 2024-09-20

Index Price

Jinko Solar JKM430N-54HL4R-BDV 430Wp (BiFacial) (BFR)

PV.jinko.bf.ntype.430BDV.bifacial

Product prices only visible after login. If you do not have an account, please register.

Product description

Jinko Solar JKM430N-54HL4R-BDV is a bifacial 430W photovoltaic panel. High efficiency and the ability to generate energy from both sides of the module make it an excellent choice for a variety of photovoltaic applications. Key advantages of the Jinko Solar JKM430N-54HL4R-BDV module:

- Bifacial design
- BFR technology
- High efficiency
- Lightweight construction

Technical specifications of Jinko Solar JKM430N-54HL4R-BDV:

Maximum Power (Pmpp): 430 Wp Open Circuit Voltage (Voc): 41.5 V Short Circuit Current (Isc): 10.6 A Voltage at Pmax (Vmpp): 34.2 V Current at Pmax (Impp): 12.6 A Module efficiency: 20.3%

Cell type: Monocrystalline Bifacial Dimensions: 1909 x 1134 x 35 mm

Weight: 23 kg

Warranty: 12 years on product, 25 years on linear power degradation