

## JA Solar JAM72D40 580MB (SFR) MC4 (BiFacial)

Product code: PV.jasolar.bifacial.580W



### Od ilości:

≥ 31 pcs.

Product prices only visible after login. If you do not have an account, please register.

≥ 310 pcs.

Product prices only visible after login. If you do not have an account, please register.

JA Solar JAM72D40 580MB is a bifacial 580W photovoltaic panel equipped with MC4 connectors. SFR (Strong Frame Removal) technology ensures the module's lightness and durability, making it an excellent choice for large photovoltaic systems requiring high energy efficiency.

Key advantages of the JA Solar JAM72D40 580MB module:

- Bifacial design
- High efficiency
- MC4 connectors
- Weather resistance

Technical specifications of JA Solar JAM72D40 580MB:

Maximum Power (P<sub>mp</sub>): 580 Wp

Open Circuit Voltage (V<sub>oc</sub>): 49.5 V

Short Circuit Current (I<sub>sc</sub>): 11.9 A

Voltage at P<sub>max</sub> (V<sub>mp</sub>): 41.5 V

Current at P<sub>max</sub> (I<sub>mp</sub>): 14.0 A

Module efficiency: 21.8%

Cell type: Monocrystalline Bifacial

Dimensions: 2285 x 1134 x 35 mm

Weight: 29 kg

Warranty: 12 years on product, 25 years on linear power degradation

## Product variants

Index

Price

**JA Solar JAM72D40 580MB (SFR) MC4 (BiFacial)**  
**PV.jasolar.bifacial.580W**

Product prices only visible after login. If you do not have an account, please register.

## Product description

JA Solar JAM72D40 580MB is a bifacial 580W photovoltaic panel equipped with MC4 connectors. SFR (Strong Frame Removal) technology ensures the module's lightness and durability, making it an excellent choice for large photovoltaic systems requiring high energy efficiency.

Key advantages of the JA Solar JAM72D40 580MB module:

- Bifacial design
- High efficiency
- MC4 connectors
- Weather resistance

Technical specifications of JA Solar JAM72D40 580MB:

Maximum Power (P<sub>mpp</sub>): 580 Wp

Open Circuit Voltage (V<sub>oc</sub>): 49.5 V

Short Circuit Current (I<sub>sc</sub>): 11.9 A

Voltage at P<sub>max</sub> (V<sub>mpp</sub>): 41.5 V

Current at P<sub>max</sub> (I<sub>mpp</sub>): 14.0 A

Module efficiency: 21.8%

Cell type: Monocrystalline Bifacial

Dimensions: 2285 x 1134 x 35 mm

Weight: 29 kg

Warranty: 12 years on product, 25 years on linear power degradation