

# Compliance Document

No. D 114387 0046 Rev. 01

**Holder of Certificate:** **Huawei Digital Power Technologies Co., Ltd.**  
Office 01, 39th Floor, Block A  
Antuoshan Headquarters Towers  
33 Antuoshan 6th Road, Futian District  
518043 Shenzhen  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Converter**  
**(Solar Inverter & Hybrid Inverter)**

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64290223058702

**Date,** 2023-09-22



( Billy Qiu )

# Compliance Document

No. D 114387 0046 Rev. 01

**Model(s):**

**Solar Inverter models:**

**SUN2000-12KTL-M5, SUN2000-15KTL-M5,  
SUN2000-17KTL-M5, SUN2000-20KTL-M5,  
SUN2000-25KTL-M5**

**Hybrid Inverter models:**

**SUN2000-12K-MB0, SUN2000-15K-MB0,  
SUN2000-17K-MB0, SUN2000-20K-MB0,  
SUN2000-25K-MB0**

**Parameters:**

Model	SUN2000-12KTL-M5	SUN2000-15KTL-M5	SUN2000-17KTL-M5	SUN2000-20KTL-M5	SUN2000-25KTL-M5
PV terminal parameters					
Maximum DC input voltage	1100 Vd.c.				
Rated input voltage	600 Vd.c.				
MPPT range	200~1000 Vd.c.				
MPPT range (full load)	370~800 Vd.c.	410~800 Vd.c.	440~800 Vd.c.	480~800 Vd.c.	530~800 Vd.c.
Maximum input current	2*30 Ad.c.				
Isc PV	2*40 Ad.c.				
Maximum input power	18000 W	22500 W	25500 W	30000 W	37500 W
Grid terminal parameters					
Rated AC voltage	230/400 Va.c., 3W+N+PE				
Rated AC output current	17.3 Aa.c.	21.7 Aa.c.	24.5 Aa.c.	28.9 Aa.c.	36.1 Aa.c.
Maximum AC output current	20.2 Aa.c.	25.2 Aa.c.	28.6 Aa.c.	33.6 Aa.c.	42.0 Aa.c.
Rated output active power	12000 W	15000 W	17000 W	20000 W	25000 W
Maximum continuous output apparent power	13200 VA	16500 VA	18700 VA	22000 VA	27500 VA
Rated AC frequency	50 Hz				
Power factor	0.8 inductive(under-excited) to 0.8 capacitive(over-excited)				

# Compliance Document

No. D 114387 0046 Rev. 01

Model	SUN2000-12K-MB0	SUN2000-15K-MB0	SUN2000-17K-MB0	SUN2000-20K-MB0	SUN2000-25K-MB0
Battery input/output parameters					
Battery type	Li-ion				
Rated voltage	600 Vd.c.				
Battery voltage range	600-980 Vd.c.				
Maximum charge/discharge current	26.25 Ad.c./26.25 Ad.c.				
Maximum charge power	25000 W	25000 W	25000 W	25000 W	25000 W
Maximum discharge power	13200 W	16500 W	18700 W	22000 W	25000 W
Maximum charge power from grid to battery	13200 W	15000 W	15000 W	15000 W	15000 W
PV terminal parameters					
Maximum DC input voltage	1100 Vd.c.				
Rated input voltage	600 Vd.c.				
MPPT Range	200~1000 Vd.c.				
MPPT Range (full load)	370~800 Vd.c.	410~800 Vd.c.	440~800 Vd.c.	480~800 Vd.c.	530~800 Vd.c.
Maximum Input Current	2*30 Ad.c.				
Isc PV	2*40 Ad.c.				
Maximum Input Power	18000 W	22500 W	25500 W	30000 W	37500 W
Grid terminal parameters					
Rated AC voltage	230/400 Va.c., 3W+N+PE				
Maximum continuous input current	19.1 Aa.c.	21.7 Aa.c.			
Maximum continuous input power	13200 W	15000 W			
Rated AC output current	17.3 Aa.c.	21.7 Aa.c.	24.5 Aa.c.	28.9 Aa.c.	36.1 Aa.c.
Maximum AC output current	20.2 Aa.c.	25.2 Aa.c.	28.6 Aa.c.	33.6 Aa.c.	42.0 Aa.c.
Rated output active power	12000 W	15000 W	17000 W	20000 W	25000 W
Maximum continuous output apparent power	13200 VA	16500 VA	18700 VA	22000 VA	27500 VA
Rated AC frequency	50 Hz				
Power factor	0.8 inductive(under-excited) to 0.8 capacitive(over-excited)				

**Tested according to:**

EN 50549-1:2019/AC:2019